



Pro Grund Primer

Pro Grund is intended for priming highly absorbing surfaces indoors, such as plaster, concrete, wood fibre boards and fibre glass. The product is less suitable for jute fabrics and sea grass wallpaper.

Pro paint carries the top coat layers in an excellent way, has very good surface adhesion and help to make joints and fillings even.

The product is suitable as primer on most surfaces; beneath wall paint that is glossier and before hanging wall papers.

Pro Grund is produced in Sweden.

Pre-painting

- Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.
- The use of correct tools and a carefully performed base is the foundation for a successful result. Do not paint if it is below +5°C.
- Make sure to protect floors and furniture before starting to paint.
- The surface must be clean, dry and firm. Wash previous painted surfaces with paint washing liquid and rinse with water. Chalky bases, as distempred ceilings, should be washed and thereafter primed with Blocka sealer before painting.

Painting

- Apply 1–2 times with roller, brush or – after dilution – with sprayer to achieve full cover. Since the product has high dry solid contents it provides very good cover ability.
- Pro Grund is the correct product to use when it comes to avoiding a variety of gloss when the surface differs in quality and structure.

Post-painting

- Wipe off the tools thoroughly before cleaning with water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, we do.

Technical data

Use	Indoors	Class of flammability	Not flammable
Binder	Styrene acrylic	Storage time	2 years if unopened, frost free storage
Gloss	2–3 (fully matt)	Air/surface temperature by painting	Minimum. +5°C
VOC-Category	(Cat. A/a): 30 g/l (2010)	Consumption	5–9 m ² /L.
Cleaning of tools	Water	Application tools	Brush, roller and (after dilution) spray
Solvent/Dilution	Water	Package	1, 3 and 10 Litres
Drying time	1 hour dust dry	In stock	Yes
(depending on air/surface temp)	2–3 hours re-paintable		



The information in this data sheet is based on laboratory tests and practical experience. Since the conditions, under which the product is used, are beyond our control, we can only guarantee the quality of the product itself. The end-result depends on the surface, preparation, temperature, humidity and execution etc.

Please check our web site to make sure that this Product data sheet is valid.